



# Matthews Paint Product Reference Guide: VOC High Solids

## Low VOC Hi-Solid (VOC) Intermix Colors

VOC202SP White	VOC911SP Violet	VOC912SP Maroon	VOC913SP Magenta	VOC914SP Dark Red	VOC915SP Red Oxide	VOC917SP Yellow Oxide	VOC920SP Blue
VOC921SP Green	VOC923SP Black	VOC925SP New Blue	VOC930SP Light Red	VOC940SP Red Yellow	VOC942SP Green Yellow	VOC947SP Scarlet Red	

### Required Catalyst 283800SP:

Choose one of the below reducers depending on you local regulations regarding VOC's

#### Required Reducer Choices for 3.5 VOC:

- **6300SP** Fast / Cool Temp reducer 60° F - 75° F / 16° C - 24° C
- **6301SP** Medium / Warm Temp reducer 70° F - 80° F / 21° C - 27° C
- **6302SP** Slow / Hot Temp reducer 75° F - 85° F / 25° C - 29° C

#### Required Reducer Choices for 2.8 VOC:

- **6370SP** Fast / Cool Temp reducer 60° F - 75° F / 16° C - 24° C
- **6371SP** Medium / Warm Temp reducer 70° F - 80° F / 21° C - 27° C
- **6372SP** Slow / Hot Temp reducer 75° F - 85° F / 25° C - 29° C

Mix ratio: 3:1:1 = 3 parts paint, 1 part catalyst & 1 part reducer.



# Matthews Paint Product Reference Guide: VOC High Solids

## Low VOC Hi-Solid (VOC) Intermix Colors with Metallic Colors

VOC202SP White	VOC911SP Violet	VOC912SP Maroon	VOC913SP Magenta	VOC914SP Dark Red	VOC915SP Red Oxide	VOC917SP Yellow Oxide	VOC920SP Blue
VOC921SP Green	VOC923SP Black	VOC925SP New Blue	VOC930SP Light Red	VOC940SP Red Yellow	VOC942SP Green Yellow	VOC947SP Scarlet Red	
VOC951SP Medium Silver	VOC952SP Sparkle Silver	VOC953SP Super Sparkle Silver	VOC954SP Fine Silver	VOC931SP Trans Red Oxide	VOC932SP Trans Yellow Oxide		

### Required Catalyst 283800SP:

Choose one of the below reducers depending on you local regulations regarding VOC's

#### Required Reducer Choices for 3.5 VOC:

- **6300SP** Fast / Cool Temp reducer 60° F - 75° F / 16° C - 24° C
- **6301SP** Medium / Warm Temp reducer 70° F - 80° F / 21° C - 27° C
- **6302SP** Slow / Hot Temp reducer 75° F - 85° F / 25° C - 29° C

#### Required Reducer Choices for 2.8 VOC:

- **6370SP** Fast / Cool Temp reducer 60° F - 75° F / 16° C - 24° C
- **6371SP** Medium / Warm Temp reducer 70° F - 80° F / 21° C - 27° C
- **6372SP** Slow / Hot Temp reducer 75° F - 85° F / 25° C - 29° C

Mix ratio: 3:1:1 = 3 parts paint, 1 part catalyst & 1 part reducer.